



CGC

IC- CUSHION LPG
13,500 / 15,500 lbs.
(6,000 / 7,000 kg)

STANDARD SPECIFICATIONS

60/70

Manufacturer's Designation		CGC60	CGC70
Load Capacity / Rated Load	lbs(kg)	13,500 (6,000)	15,500 (7,000)
Height Overhead Guard	in(mm)	91.0 (2311)	91.0 (2311)
Width	in(mm)	58.8 (1494)	58.8 (1494)
Right Angle Stack (add load length & clearance)	in(mm)	STD 124.0 (3149) / TSU 124.8 (3170)	STD 126.3 (3208) / TSU 127.1 (3228)
Outside Turning Radius	in(mm)	105.1 (2669)	107.4 (2728)
Travel Speed Loaded / Unloaded	mph (kph)	10.3/10.4 (16.5/16.5)	10.2/10.4 (16.3/16.6)
Power Unit	HP(KW) @ rpm	PSI-4X 4.3L 110 (82) @ 2400	PSI-4X 4.3L 110 (82) @ 2400

STANDARD FEATURES

- **PSI-4X 4.3L V6 Engine • EPA Compliant • Standard and Triple Uprights • Full Range of Lift Heights**
- **High Visibility “Silent Staging” Uprights • Two Speed Powershift Transmission • Power Steering • Tilt Steering Wheel • Rear Handle with Horn Button • Full Suspension Vinyl Safety Seat • Orange Seatbelt • Traction Disable Seat Switch • Operator Presence System • Power Assisted Disc Brakes • Open Core Radiator • High Air Intake • Heavy Duty Air Cleaner • Tow Pin • Automatic Engine Shutdown System**



For more information on this model and full line of CLARK Forklifts, find your local CLARK Dealer at www.clarkmhc.com